

Parameters Subject to Change Without Notice

DESCRIPTION

The JW[®]5079B is a monolithic buck switching regulator based on I2 architecture for fast transient response. Operating with an input range of 4V~23V, JW5079B delivers 10A of continuous output current with two integrated N-Channel MOSFETs. The internal synchronous power switches provide high efficiency without the use of an external Schottky diode. At light loads, the regulator operates in low frequency to maintain high efficiency and low output ripples.

JW5079B guarantees robustness with output short protection, thermal protection, current run-away protection, and input under voltage lockout.

JW5079B is available in QFN3×3-20 package, which provide a compact solution with minimal external components.

Company's Logo is Protected, "JW" and "JOULWATT" are Registered Trademarks of JoulWatt technology Inc.

FEATURES

- 4V to 23V operating input range
- 10A output current
- Up to 95% efficiency
- High efficiency at light load
- 650kHz frequency
- Fixed 3.3V LDO output supplies 200mA
- Input under voltage lockout
- Power good indicator
- Output discharge function
- Output Over/Under Voltage Protection
- Output short protection
- Thermal protection
- Available in QFN3X3-20 package

APPLICATIONS

- Industrial and commercial low power system
- Computer peripherals
- LDO monitors and TVs
- Green Electronics/ Appliances

TYPICAL APPLICATION

